

7" Threaded Air Angle Grinder (Safety Lever)



SPECIFICATION	R-2180LT
Wheel or Brush Size	180mm
Spindle Thread	5/8" – 11 Male Spindle
Maximum Speed	6,000 rpm
Net Weight	3.7 kg
Length	360 mm
Air Consumption	0.75m ³ /min
Air Inlet	3/8"
Hose Size	12.7 mm
Sound Pressure	91 dBA
Air Pressure	90 psi
Vibration	< 2.5m/S ²

MODEL: R-2180LT

FEATURES

- Designed as lightweight powerful tool for tough, tight, quarter cleaning jobs that require fast metal removal.
- Tough alloy housing for heavy and long lasting operation.
- Adjustable wheel guard.
- Heavy duty ball bearing for minimum vibration.
- Removal side-handle for access to tight quarters.
- Lever throttle for safety operation.
- 5/8"-11 male spindle for easy, fast mounting of 5/8"-11 threaded nut abrasive wheels and wire brushes.

7" Air Angle Grinder (Safety Lever)



SPECIFICATION	R-2180L
Wheel or Brush Size	180mm
Spindle Thread	5/8" – 11
Maximum Speed	7,000 rpm
Net Weight	3.05 kg
Length	331 mm
Air Consumption	0.93m ³ /min
Air Inlet	3/8"
Hose Size	11.0mm
Sound Pressure	88 dBA
Air Pressure	90 psi
Vibration	< 3.2 m/S ²

MODEL: R-2180L

FEATURES

- Designed as lightweight powerful tool for tough, tight, quarter cleaning jobs that require fast metal removal.
- Aluminium alloy housing for lightweight and operator comfort.
- Adjustable wheel guard.
- Heavy duty ball bearing for minimum vibration.
- Removable side-handle for access to tight quarters.
- Lever throttle for safety operation.

Pneumatic Tools

4" Air Angle Grinder (Safety Lever)



SPECIFICATION	R-2100L
Wheel Size	100mm
Spindle Thread	3/8" – 24
Maximum Speed	12,000 rpm
Net Weight	1.69 kg
Length	226 mm
Air Consumption	0.65m ³ /min
Air Inlet	1/4"
Hose Size	8.0 mm
Sound Pressure	86 dBA
Air Pressure	90 psi
Vibration	< 2.5 m/S ²

MODEL: R-2100L

FEATURES

- Designed as lightweight powerful tool for tough, tight, quarter cleaning jobs that require fast metal removal.
- Aluminium alloy housing for lightweight and operator comfort.
- Heavy duty ball bearing for minimum vibration.
- Compact design for ease of handling.
- Removal side-handle for access to tight quarters.
- Wheel guard for added safety.
- Lever throttle for safety operation.
- Available in 4" diameter Throttle Grip Type: **Model: R-2100G.**

5" Air Angle Grinder (Safety Lever)



SPECIFICATION	R-2125L
Wheel Size	125mm
Spindle Thread	M14
Maximum Speed	11,000 rpm
Net Weight	1.75 kg
Length	226 mm
Air Consumption	0.45m ³ /min
Air Inlet	1/4"
Hose Size	8.0 mm
Sound Pressure	86 dBA
Air Pressure	90 psi
Vibration	< 2.5 m/S ²

MODEL: R-2125L

FEATURES

- Designed as lightweight powerful tool for tough, tight, quarter cleaning jobs that require fast metal removal.
- Aluminium alloy housing for lightweight and operator comfort.
- Heavy duty ball bearing for minimum vibration.
- Compact design for ease of handling.
- Removal side-handle for access to tight quarters.
- Wheel guard for added safety.
- Lever throttle for safety operation.

Air Die Grinder



SPECIFICATION	R-2006
Collet Size	6mm (1/4")
Maximum Speed	22,000 rpm
Net Weight	0.6 kg
Length	168 mm
Air Consumption	0.22 ³ /min
Air Inlet	1/4"
Hose Size	5.0mm
Sound Pressure	90 dBA
Air Pressure	90 psi
Vibration	< 2.5 m/S ²

MODEL: R-2006

FEATURES

- Compact and lightweight for ease of use.
- Ball bearing construction for long tool life.
- Hardened steel components for durability.
- Rear exhaust directs air away from work.

Air Needle Scaler / Flux Chipper (2 in 1)



SPECIFICATION	R-2801
Needle Size and Quantity	3 mm x 19
Stroke Speed	4,000 bpm
Net Weight	2.69 kg
Length	212 mm
Air Consumption	0.12m ³ /min
Air Inlet	1/4"
Hose Size	8.0 mm
Sound Pressure	90 dBA
Air Pressure	90 psi
Vibration	< 14.5 m/S ²

MODEL: R-2801

FEATURES

- Smooth action throttling.
- Chisels are changed easily by a quick release mechanism.
- Needle Scaler attachment is easily inter-changeable with chisel.

Air Flux Chipper



SPECIFICATION	R-2800
Stroke Speed	4,400 rpm
Net Weight	1.73 kg
Length	212 mm
Air Consumption	0.12 ³ /min
Air Inlet	1/4"
Hose Size	8.0mm
Air Pressure	90 psi

MODEL: R-2800

FEATURES

- Lightweight and Heavy Duty.
- Chisels are cinterchangeable easily by a quick release mechanism.

OPTIONAL

- Straight chisel is also available as an optional accessory.

6" Heavy Duty Air Straight Grinder



SPECIFICATION	R-2811
Suitable Disc Wheel Size	150 mm
Maximum Speed	5,700 bpm
Net Weight	5.16 kg
Length	500 mm
Air Consumption	0.49m ³ /min
Air Inlet	1/2"
Hose Size	9,5 mm
Sound Pressure	87 dBA
Air Pressure	90 psi
Vibration	< 2.5 m/S ²

MODEL: R-2811

FEATURES

- Powerful and heavy duty design.
- Ergonomically designed grip handle for ease of use.